

# VC-51MX2-M/C30 I

Ultra High Resolution CMOS Digital Camera



CoaXPRESS®

The VC-51MX2-M/C30I00 is a new 51-megapixel CoaXPRESS camera based on GMAX4651, the latest CMOS image sensor technology, from Gpixel. It offers up to 30 frames per second at 8,416 × 6,032 resolution. The camera comes with the next generation CoaXPRESS 2.0 (CXP-12) interface, delivering up to 50 Gigabits per second over 4 coaxial cables. With advanced uniformity and high-speed image processing capabilities, it sets a new standard for high-performance digital imaging in industrial, scientific, and surveillance fields. This camera is ideal for demanding applications such as FPD, PCB, and semiconductor inspections.

# VC-51MX2-M/C30I00

Ultra High Resolution CMOS Digital Camera

## Main Features

- 51-Megapixel Resolution
- CoaXPress 2.0 Interface up to 30 fps at 50 Gbps using 4 Channels
- Power over CoaXPress (PoCXP)
- Global Shutter CMOS Technology
- DSNU and PRNU Correction
- Flat Field Correction
- Defective Pixel Correction

## Applications

- Flat Panel Display Inspection
- Electronics Inspection
- Semiconductor Inspection
- Document / Film Scanning


## Specifications

Model		VC-51MX2-M/C30I00
Resolution (H × V)		8,416 × 6,032
Sensor		GMAX4651
Sensor Size (Diagonal)		38.8 mm × 27.8 mm (47.63 mm)
Pixel Size		4.6 μm × 4.6 μm
Interface		CoaXPress 2.0 (CXP-6/10/12)
Max. Frame Rate (8 bit)		30.3 fps
Exposure Time (1 μs step)		1 μs to 20 s
Binning		Horizontal and Vertical Independent: ×1, ×2, and ×4(Mono Only)
Pixel Data Format	Monochrome	8/10/12 bit
	Color	RG Bayer 8/10/12 bit
Electronic Shutter		Global Shutter
Exposure Mode		Timed, Trigger Width
Dynamic Range		65 dB at 12 bit
Gain Control	Analog	×3.5 to ×5
	Digital	×1 to ×32
Black Level Control		0 to 256 LSB at 12 bit
Dimension / Weight	FAN	68 mm × 68 mm × 79 mm, 0.47kg
	Heatsink	168 mm × 68 mm × 83 mm, 0.45kg
Temperature		Operating: 0°C to 40°C, Storage: -40°C to 70°C
Trigger Synchronization		Free-Run, Hardware Trigger, Software Trigger, and CXP
External Trigger		3.3 V to 24.0 V, 10 mA, Logical Level Input, Optically Isolated
Software Trigger		Asynchronous, Programmable via Camera API
Lens Mount		M58 mount, F-mount adapter, or custom mount available upon request
Power	External	11 to 24 V DC
	Dissipation	Typ.11.5 W
	PoCXP	24 V DC, Minimum 2 of PoCXP cables required
Compliance		CE, FCC, KC
API SDK		Vieworks Imaging Solution 7.X


# VC-51MX2-M/C30I00

Ultra High Resolution CMOS Digital Camera

## Spectral Response



## Ordering Scheme



## Connector Specification

### Power



1, 2, 3: +12V DC  
4, 5, 6: GND  
(HR10A-7R-6PB)


### Control



1: Trigger IN+  
2: Trigger IN-  
3: Strobe Out-(GND)  
4: Strobe Out+  
(HR10A-7R-4S)

### Data Transfer / Communications

Micro-BNC



CH1 CH2 CH3 CH4

CH1: Master Connection  
75 Ω, Micro-BNC (HD-BNC)

Connectors on camera body


# VC-51MX2-M/C30I00

Ultra High Resolution CMOS Digital Camera


## Mechanical Dimensions

Unit: mm

### VC-51MX2 (FAN)



### VC-51MX2 (Heatsink)



sales@visionsystemtech.com